

26 OCT 2004

(19) World Intellectual Property Organization  
International Bureau(43) International Publication Date  
27 November 2003 (27.11.2003)

PCT

(10) International Publication Number  
WO 03/097745 A1(51) International Patent Classification<sup>7</sup>: C08L 83/04,  
101/10, 69/00

(21) International Application Number: PCT/US03/15331

(22) International Filing Date: 15 May 2003 (15.05.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
60/381,654 16 May 2002 (16.05.2002) US

(71) Applicants (for all designated States except US): DOW CORNING CORPORATION [US/US]; 2200 West Salzburg Road, Midland, MI 48686-0994 (US). DOW CORNING TORAY SILICONE CO., LTD. [JP/JP]; 4th Floor, AIG Building, 1-1-3, Marunouchi, Chiyoda-ku, Tokyo 100-0005 (JP).

(72) Inventors; and

(75) Inventors/Applicants (for US only): ROMENESKO, David [US/US]; 4102 Elm Court, Midland, MI 48642 (US). SCHMIDT, Randall [US/US]; 813 Honeysuckle Circle, Midland, MI 48642 (US). TOGASHI, Atsushi [JP/JP]; 3-7-15-303 Nobuto, Cho-ku, Chiba-shi, Chiba Prefecture 260-0032 (JP). WIEBER, Gary [US/US]; 4407 Huron Drive, Midland, MI 48642 (US).

(74) Common Representative: DOW CORNING CORPORATION; TROY, Timothy, Patent Department - Mail CO1232, 2200 West Salzburg Road, Midland, MI 48686-0994 (US).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,

GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

## Declarations under Rule 4.17:

— as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for all designations

— as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

— of inventorship (Rule 4.17(iv)) for US only

## Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: FLAME RETARDANT COMPOSITIONS

(57) Abstract: This invention relates to a flame retardant composition comprising: (a) 81 to 99.99 weight percent of a thermoplastic resin, thermoset resin, thermoplastic resin blend, or thermoset resin blend which upon burning forms a char and (b) 0.01-19 weight percent of a silsesquioxane resin having a weight average molecular weight of greater than 300 and having the average molecular formula:  $(R_2SiO_{1/2})_a(R_2SiO_{2/2})_b(RSiO_{3/2})_c(SiO_{4/2})_d(RO_{1/2})_e(OH_{1/2})_f$  wherein each R is hydrogen, an alkyl group, an alkenyl group, or an aryl group having from 6 to 12 carbon atoms, a and b are zero or positive numbers and the value of a+b is greater than zero, c is a positive number, d, e and f are zero or positive numbers with the provisos that the copolymer comprises at least 40 mole percent of  $R_2SiO_{3/2}$  units, the copolymer comprises less than 10 mole percent  $SiO_{4/2}$  units, greater than 30 mole percent of the silicon-bonded R groups are silicon-bonded aryl groups, greater than 0.5 mole percent of the silicon-bonded R groups are silicon-bonded hydrogen atoms, the content of silicon-bonded hydroxyl groups is equal to or less than 2 weight percent, and the content of silicon-bonded alkoxy groups where the alkoxy group is methoxy or ethoxy is equal to or less than 5 weight percent.

BEST AVAILABLE COPY